

PARALLEL CONNECTOR, INSULATED, CROSS-SECTION 1.5 - 2.5 MM²
Article number: 180322

Parallel connector, insulated- Technical data: Material: Cu-ETP according to DIN EN 13600 - Surface: electro-tinned - For strain-relieved connections - Insulation PVC/PE - Temperature resistance -40°C to +70°C. Cross section 1.5-2.5 mm², insulation material: PVC; insulation color: blue; L1: 19; L2: 8 D1: 2.3; weight per 100 pcs ~kg: 0.06; UL listed: x; PU/pc. 100.



Length (mm)	150 mm
Width (mm)	85 mm
Height (mm)	7 mm
Weight (kg)	0,00087 kg

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Execution	Normalausführung
Connection type	Parallelverbinder
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Sleeve shape	kurz
Insulation	Polyamid (PA)
Nominal cross-section	1.5 mm ² - 2.5 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Color of the insulation	blau
Oil stop/center bar	No
Voltage series	bis 230/380 V
Number of branches	2
Rated current	- A

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



GTIN: 4021103803226

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de