

## BUTT CONNECTOR WITH SHRINK INSULATION 1.5 - 2.5 MM<sup>2</sup>

### Article number: 180342

Butt connector with shrink insulation - Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro-tinned - For strain-relieved connections - Insulation polyolefin with inner coating of hot-melt adhesive - Shrink temperature: +150° C - Temperature resistance -10°C to +105°C - After shrinking, the hot-melt adhesive forms an insulating, ageing-resistant, strain-relieving and waterproof connection; not suitable for solid conductors. Cross-section: 1.5-2.5 mm<sup>2</sup>; insulation color: blue; L1: 37; L2: 15; D1: 2.3; weight per 100 pcs ~kg: 0.15; PU/pc. 100.



Length (mm)	175 mm
Width (mm)	100 mm
Height (mm)	18 mm
Weight (kg)	0,00128 kg

Attribute	Value
Color	blau
Halogen-free	Yes
AWG range	13 - 15
Nominal cross-section	1.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup>

GTIN: 4021103803424

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de