

**BUTT CONNECTORS WITH SHRINK INSULATION 4 - 6 MM<sup>2</sup>****Article number: 180346**

Butt connector with shrink insulation - Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro-tinned - For strain-relieved connections - Insulation polyolefin with inner coating of hot-melt adhesive - Shrink temperature: +150° C - Temperature resistance -10°C to +105°C - After shrinking, the hot-melt adhesive forms an insulating, ageing-resistant, strain-relieving and waterproof connection; not suitable for solid conductors. Cross section: 4-6 mm<sup>2</sup>; insulation color: yellow; L1: 42; L2: 15; D1: 3,6; weight per 100 pcs ~kg: 0,25; PU/pc. 50.



Length (mm)	180 mm
Width (mm)	100 mm
Height (mm)	18 mm
Weight (kg)	0,0022 kg

Attribute	Value
Color	gelb
Halogen-free	Yes
AWG range	9 - 11
Nominal cross-section	4 mm <sup>2</sup> - 6 mm <sup>2</sup>

GTIN: 4021103803462

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de