

CRIMP CABLE LUG, RING SHAPE CU, DIN 46234, CONDUCTOR CROSS-SECTION/CONNECTION STUD 70 MM²/6 MM Ø

Article number: 180478

Crimp terminals, ring type Cu, DIN 46234. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - Especially suitable for fine stranded conductors according to IEC 228. Cross-section: 70 mm²; bolt-Ø 6 mm; nominal size according to DIN: 6-70; D1: 13; D3: 6,5; A: 18; B: 22; L: 38; S: 2; weight per 100 pcs ~kg: 2,7; PU/pc: 1.



Length (mm)	180 mm
Width (mm)	100 mm
Height (mm)	43 mm
Weight (kg)	0,027 kg

Attribute	Value
Connection thread dimension (metric)	6
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	0 - 0
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Ringform
Insulation	ohne
Nominal cross-section	70 mm ² - 70 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Maximum current (I _{max})	- A

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103804780

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de