

## CRIMP CABLE LUG, RING SHAPE CU, DIN 46234, CONDUCTOR CROSS-SECTION/CONNECTION STUD 70 MM<sup>2</sup>/12 MM Ø

**Article number: 180484**

Crimp terminals, ring type Cu, DIN 46234. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - Especially suitable for fine stranded conductors according to IEC 228 . Cross section: 70 mm<sup>2</sup>; Bolt-Ø 12 mm; Nominal size according to DIN: 12-70; D1: 13; D3: 13; A: 22; B: 38; L: 38; S: 2; Weight per 100 pcs ~kg: 2,4; Packs/pcs: 1



Length (mm) 170 mm  
 Width (mm) 100 mm  
 Height (mm) 37 mm  
 Weight (kg) 0,024 kg

Attribute	Value
Connection thread dimension (metric)	12
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	0 - 0
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Ringform
Insulation	ohne
Nominal cross-section	70 mm <sup>2</sup> - 70 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Maximum current (I <sub>max</sub> )	- A

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103804841

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de