

**CRIMP CABLE LUG, RING SHAPE CU, DIN 46234, CONDUCTOR CROSS-SECTION/CONNECTION STUD 120 MM<sup>2</sup>/16 MM Ø,**
**Article number: 180502**

Crimp terminals, ring type Cu, DIN 46234. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - Especially suitable for fine stranded conductors according to IEC 228. Cross-section: 120 mm<sup>2</sup>; bolt-Ø 16 mm; nominal size according to DIN: 16-120; D1: 17; D3: 17 A: 22; B: 28; L: 48; S: 3; weight per 100 pcs ~kg: 5,8; PU/pc: 1.



Length (mm)	180 mm
Width (mm)	100 mm
Height (mm)	23 mm
Weight (kg)	0,058 kg

Attribute	Value
Connection thread dimension (metric)	16
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Ringform
Insulation	ohne
Nominal cross-section	120 mm <sup>2</sup> - 120 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Maximum current (I <sub>max</sub> )	- A
Flange length	- mm

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103805022

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de