

CRIMP CABLE LUG, RING SHAPE CU, DIN 46234, CONDUCTOR CROSS-SECTION/CONNECTION STUD 150 MM²/10 MM Ø,
Article number: 180504

Crimp terminals, ring type Cu, DIN 46234. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - Especially suitable for fine stranded conductors according to IEC 228. Cross-section: 150 mm²; bolt-Ø 10 mm; nominal size according to DIN: 10-150; D1: 19; D3: 10,5; A: 24; B: 30; L: 50; S: 3,2; weight per 100 pcs. ~kg: 7,7; packing unit: 1.



Length (mm)	180 mm
Width (mm)	100 mm
Height (mm)	27 mm
Weight (kg)	0,077 kg

Attribute	Value
Connection thread dimension (metric)	10
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Ringform
Insulation	ohne
Nominal cross-section	150 mm ² - 150 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Maximum current (I _{max})	- A
Flange length	- mm

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103805046

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de