

**FORKED CABLE LUG, CONDUCTOR CROSS-SECTION/CONNECTION BOLT 4 - 6 MM<sup>2</sup>/5 MM Ø**
**Article number: 180542**

Crimp cable lug, fork form Cu. Technical data- Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Sleeve seam hard soldered - For strain relieved connections. Cross-section: 4-6 mm<sup>2</sup>; bolt-Ø: 5; D1: 3,6; D3: 5,3; A: 6; B: 10,0; L: 15; S: 1; weight per 100 pcs. ~kg: 0,16; PU/pc.: 100.

Length (mm)	150 mm
Width (mm)	90 mm
Height (mm)	9 mm
Weight (kg)	0,0016 kg



Attribute	Value
Connection thread dimension (metric)	5
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	10 - 12
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Gabelform
Insulation	ohne
Nominal cross-section	4 mm <sup>2</sup> - 6 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Maximum current (I <sub>max</sub> )	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de



|

GTIN: 4021103805428

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de