

CRIMP CABLE LUG IN PIN FORM CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/PIN 1.5 - 2.5 MM²/2.3 MM Ø

Article number: 180592

Crimp terminals, pin form Cu, 0.5-6 mm² according to DIN. Technical data; material: Cu-ETP according to DIN EN 13600; surface: electro tin plated ; sleeve seam hard soldered; for strain relieved connection. Cross-section: 1.5-2.5; Pin-Ø: 2.3 mm; L1: 17; L2: 10; D1: 2.3; A: 5; B: 1.9; S: 0.8; Weight per 100pcs:~kg: 0.07; Packs per unit: 100

Length (mm)	150 mm
Width (mm)	90 mm
Height (mm)	7 mm
Weight (kg)	0,00071 kg



Attribute	Value
Surface protection	vernickelt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	14 - 16
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Stiftform
Insulation	ohne
Nominal cross-section	1.5 mm ² - 2.5 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Maximum current (I _{max})	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Pin diameter (pin cable lug) | - mm

GTIN: 4021103805923

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de