

**CRIMP CABLE LUG IN PIN FORM CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/PIN 25 MM<sup>2</sup>/7 MM Ø**
**Article number: 180604**

Crimp terminals, pin form Cu, 0.5-6 mm<sup>2</sup> according to DIN. Technical data; material: Cu-ETP according to DIN EN 13600; surface: electro tin plated ; sleeve seam hard soldered; for strain relieved connection. Cross section: 25; Pin-Ø: 7 mm; L1: 33,5; L2: 15; D1: 6,7; A: 13,5; B: 6,8; S: 1,2; Weight per 100pcs:~kg: 0,66; Packs per unit: 100

|             |           |
|-------------|-----------|
| Length (mm) | 180 mm    |
| Width (mm)  | 100 mm    |
| Height (mm) | 45 mm     |
| Weight (kg) | 0,0066 kg |



| Attribute                                     | Value                                   |
|---|---|
| Surface protection                            | vernickelt                              |
| Material                                      | Kupfer                                  |
| Halogen-free                                  | Yes                                     |
| Strip goods                                   | No                                      |
| Total length                                  | - mm                                    |
| AWG range                                     | 4 - 4                                   |
| Suitable for solid conductors                 | No                                      |
| Suitable for stranded conductors              | Yes                                     |
| Suitable for fine-stranded conductors         | Yes                                     |
| Corresponds to DIN                            | Yes                                     |
| Sleeve shape                                  | kurz                                    |
| Flange shape                                  | Stiftform                               |
| Insulation                                    | ohne                                    |
| Nominal cross-section                         | 25 mm <sup>2</sup> - 25 mm <sup>2</sup> |
| For tensile strength connections              | No                                      |
| Suitable for round conductors                 | Yes                                     |
| Suitable for high temperatures (up to 650 °C) | No                                      |
| Suitable for flat conductors                  | No                                      |
| Suitable for enameled wire                    | No                                      |
| Maximum current (I <sub>max</sub> )           | - A                                     |
| Flange length                                 | - mm                                    |
| Pin width (flat pin cable lug)                | - mm                                    |

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

Pin diameter (pin cable lug) | - mm

GTIN: 4021103806043

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de