

TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 4 MM²/6 MM Ø
Article number: 180684

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross section: 4 mm²; bolt Ø: 6; W: 12; Øi: 2,7; Øe: 5; C1: 6,2; C2: 7,4; a: 9; L: 26; weight per 100pcs ~kg: 0,28; 7 mm: - ; compression 5 mm: 1; pack per unit: 100.



Length (mm)	160 mm
Width (mm)	100 mm
Height (mm)	8 mm
Weight (kg)	0,00282 kg

Attribute	Value
Connection thread dimension (metric)	6
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	4 mm ²
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	12
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	verschiedene

GTIN: 4021103806845

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de