

TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 50 MM²/14 MM Ø
Article number: 180745

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross-section: 50 mm²; stud-Ø: 14; W: 23; Øi: 10; Øe: 14; C1: 14; C2: 14,5; a: 19; L: 56,5; weight per 100pcs ~kg: 3,18; 7 mm: 1; compression 5 mm: 2; PU/pc: 1.



Length (mm)	57 mm
Width (mm)	23 mm
Height (mm)	14 mm
Weight (kg)	0,0318 kg

Attribute	Value
Connection thread dimension (metric)	14
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	50 mm ²
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	1
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	verschiedene

GTIN: 4021103807453

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de