

TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 120 MM²/16 MM Ø
Article number: 180774

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross-section: 120 mm²; stud-Ø: 16; W: 30; Øi: 15; Øe: 19,5; C1: 15,5; C2: 16; a: 26; L: 70,5; weight per 100pcs ~kg: 6,52; 7 mm: 1; compression 5 mm: 2; PU/pc: 1.



Length (mm)	71 mm
Width (mm)	30 mm
Height (mm)	20 mm
Weight (kg)	0,06523 kg

Attribute	Value
Connection thread dimension (metric)	16
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	120 mm ²
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	250 kcmil
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	verschiedene

GTIN: 4021103807743

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de