

**TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 185 MM<sup>2</sup>/12 MM Ø**
**Article number: 180790**

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross-section: 185 mm<sup>2</sup>; stud-Ø: 12; W: 35; Øi: 19; Øe: 24; C1: 17; C2: 18; a: 30; L: 81; weight per 100pcs ~kg: 11,13; 7 mm: 2; compression 5 mm: 4; PU/pc: 1.



|             |            |
|-------------|------------|
| Length (mm) | 82 mm      |
| Width (mm)  | 35 mm      |
| Height (mm) | 24 mm      |
| Weight (kg) | 0,11127 kg |

| Attribute                            | Value               |
|--------------------------------------|---------------------|
| Connection thread dimension (metric) | 12                  |
| Connection bracket                   | 180° (horizontal)   |
| Number of fixing holes               | 1                   |
| Nominal cross-section                | 185 mm <sup>2</sup> |
| Surface protection                   | verzinkt            |
| Material                             | Kupfer              |
| Insulated                            | No                  |
| AWG size                             | 350 kcmil           |
| Narrow flange design                 | No                  |
| Flange shape                         | Ringform            |
| With viewing hole                    | No                  |
| Ladder class                         | verschiedene        |

GTIN: 4021103807903

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de