

**TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 240 MM<sup>2</sup>/12 MM Ø**
**Article number: 180800**

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross-section: 240 mm<sup>2</sup>; stud-Ø: 12; W: 39; Øi: 21; Øe: 26; C1: 17; C2: 18; a: 35; L: 88; weight per 100pcs ~kg: 13,38; 7 mm: 2; compression 5 mm: 4; PU/pc: 1.



Length (mm)	89 mm
Width (mm)	39 mm
Height (mm)	26 mm
Weight (kg)	0,13381 kg

Attribute	Value
Connection thread dimension (metric)	12
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	240 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	500 kcmil
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	verschiedene

GTIN: 4021103808009

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de