

**BUTT CONNECTOR CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/LENGTH 35 MM<sup>2</sup>/42 MM, 1  
PIECE****Article number: 180916**

Butt connector Cu, standard version. Technical data - material: Cu-ETP according to DIN EN 13600 - surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 - annealed to copper hardness F 20. cross section: 35 mm<sup>2</sup>; Øi: 8,5; Øe: 12; L: 42; weight per 100pcs ~kg: 2,11; 7 mm: 1-1; compression 5 mm: 2-2 ; Packs per unit: 1.

Length (mm)	42 mm
Width (mm)	12 mm
Height (mm)	12 mm
Weight (kg)	0,02106 kg



CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Execution	Normalausführung
Connection type	Stoßverbinder
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Sleeve shape	lang
Insulation	ohne
Nominal cross-section	35 mm <sup>2</sup> - 35 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Oil stop/center bar	No
Voltage series	bis 600 V
Number of branches	2
Rated current	- A

GTIN: 4021103809167

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de