

**BUTT CONNECTOR CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/LENGTH 120 MM<sup>2</sup>/62 MM, 1 PIECE**
**Article number: 180924**

Butt connector Cu, standard version. Technical data - material: Cu-ETP acc. to DIN EN 13600 - surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors acc. to IEC 228 - annealed to copper hardness F 20. cross section: 120 mm<sup>2</sup>; Øi: 15; Øe: 19,5; L: 62; weight per 100pcs. ~kg: 7,4; 7 mm: 1-1; compression 5 mm: 3-3; PU/pc.: 1.



Length (mm)	65 mm
Width (mm)	20 mm
Height (mm)	20 mm
Weight (kg)	0,074 kg

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Execution	Normalausführung
Connection type	Stoßverbinder
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Sleeve shape	lang
Insulation	ohne
Nominal cross-section	120 mm <sup>2</sup> - 120 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Oil stop/center bar	No
Voltage series	bis 600 V
Number of branches	2
Rated current	- A

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de



GTIN: 4021103809242

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de