

BUTT CONNECTOR CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/LENGTH 300 MM²/102 MM, 1 PIECE**Article number: 180932**

Butt connector Cu, standard version. Technical data - material: Cu-ETP according to DIN EN 13600 - surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 - annealed to copper hardness F 20. cross section: 300 mm²; Øi: 23,5; Øe: 29,5; L: 102; weight per 100pcs ~kg: 22,23; 7 mm: 2-2; compression 5 mm: - ; Packs of: 1.

Length (mm)	100 mm
Width (mm)	31 mm
Height (mm)	31 mm
Weight (kg)	0,22228 kg



CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Execution	Normalausführung
Connection type	Stoßverbinder
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Sleeve shape	lang
Insulation	ohne
Nominal cross-section	300 mm ² - 300 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Oil stop/center bar	No
Voltage series	bis 600 V
Number of branches	2
Rated current	- A

GTIN: 4021103809327

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de