

BUTT CONNECTOR CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/LENGTH 300 MM²/102 MM, 1 PIECE**Article number: 180932**

Butt connector Cu, standard version. Technical data - material: Cu-ETP according to DIN EN 13600 - surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 - annealed to copper hardness F 20. cross section: 300 mm²; Øi: 23,5; Øe: 29,5; L: 102; weight per 100pcs ~kg: 22,23; 7 mm: 2-2; compression 5 mm: - ; Packs of: 1.

| | |
|-------------|------------|
| Length (mm) | 100 mm |
| Width (mm) | 31 mm |
| Height (mm) | 31 mm |
| Weight (kg) | 0,22228 kg |



CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

| Attribute | Value |
|---|---|
| Surface protection | verzinkt |
| Material | Kupfer |
| Execution | Normalausführung |
| Connection type | Stoßverbinder |
| Suitable for solid conductors | No |
| Suitable for stranded conductors | Yes |
| Suitable for fine-stranded conductors | Yes |
| Sleeve shape | lang |
| Insulation | ohne |
| Nominal cross-section | 300 mm ² - 300 mm ² |
| For tensile strength connections | No |
| Suitable for round conductors | Yes |
| Suitable for high temperatures (up to 650 °C) | No |
| Suitable for flat conductors | No |
| Suitable for enameled wire | No |
| Oil stop/center bar | No |
| Voltage series | bis 600 V |
| Number of branches | 2 |
| Rated current | - A |

GTIN: 4021103809327

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de