


## BUTT CONNECTOR CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/LENGTH 400 MM<sup>2</sup>/102 MM, 1 PIECE

**Article number: 180934**

Butt connector Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 - annealed to copper hardness F 20. Cross section: 400 mm<sup>2</sup>;  $\varnothing$ i: 27;  $\varnothing$ e: 34; L: 102; Weight per 100pcs ~kg: 29.85; 7 mm: 2-2; compression 5 mm: - ; Packs of: 1.



Length (mm)	95 mm
Width (mm)	36 mm
Height (mm)	36 mm
Weight (kg)	0,29847 kg

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Execution	Normalausführung
Connection type	Stoßverbinder
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Sleeve shape	lang
Insulation	ohne
Nominal cross-section	400 mm <sup>2</sup> - 400 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Oil stop/center bar	No
Voltage series	bis 600 V
Number of branches	2
Rated current	- A

GTIN: 4021103809341

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de