

FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 1.0 MM²/12 MM
Article number: 180946

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 1. Technical data, material: Cu-ETP according to DIN EN 13600- surface: electro tin plated - insulation polypropylene - temperature resistance -35°C to +105°C - For easy plugging onto fine stranded copper conductors, prevents damage and splicing. Cross section: 1 mm², length without insulation L2: 12 mm; total length L1: 18 mm; D1: 1.4; S1: 0.15; S2: 0.25; D2: 3; insulation color: red; weight per 100 pcs.: 0.02; pack of 100.



Length (mm)	150 mm
Width (mm)	75 mm
Height (mm)	5 mm
Weight (kg)	0,00016 kg

Attribute	Value
Nominal cross-section	1 mm ²
Surface protection	sonstige
Material	Kupfer
Color	rot
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	18 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	12 mm
With identification flag	No
AWG size	16

GTIN: 4021103809464

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de