

FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 1.5 MM²/12 MM
Article number: 180949

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 1. Technical data, material: Cu-ETP according to DIN EN 13600- surface: electro tin plated - insulation polypropylene - temperature resistance -35°C to +105°C - For easy plugging onto fine stranded copper conductors, prevents damage and splicing. Cross section: 1.5 mm², length without insulation L2: 12 mm; total length L1: 18 mm; D1: 1.7; S1: 0.15; S2: 0.25; D2: 3.5; insulation color: black; weight per 100 pcs.: 0.02; pack of 100.



Length (mm)	145 mm
Width (mm)	100 mm
Height (mm)	6 mm
Weight (kg)	0,00016 kg

Attribute	Value
Nominal cross-section	1.5 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	schwarz
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	18 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	12 mm
With identification flag	No

GTIN: 4021103809495

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de