

## SCREW CONNECTOR, TIN-PLATED CONDUCTOR CROSS-SECTION 10-35 MM<sup>2</sup>, CU, STANDARD VERSION AND AL

**Article number: 180962**

Connection equipment - screw connectors or branch and connection terminals for kV cast resin joints, shrink joints and mechanical connection and branch joints (MVM and MAM). Screw connector type: Tin-plated with a conductor cross-section of 10 mm<sup>2</sup> to 35 mm<sup>2</sup>; Cu and AL only.

Length (mm)	40 mm
Width (mm)	14 mm
Height (mm)	14 mm
Weight (kg)	0,015 kg



Attribute	Value
Protection class (IP)	IPO0
Surface protection	verzinkt
Nominal cross-section aluminum, SE	10 mm <sup>2</sup> - 35 mm <sup>2</sup>
Number of screws	4
Oil stop/center bar	No
Voltage series	bis 15 kV
Conductor material	Aluminium/Kupfer
With soldering hole	No
Nominal cross-section copper, SM	10 mm <sup>2</sup> - 35 mm <sup>2</sup>
With insulation	No
Nominal cross-section copper, RM	10 mm <sup>2</sup> - 35 mm <sup>2</sup>
Nominal cross-section copper, RE	10 mm <sup>2</sup> - 50 mm <sup>2</sup>
Nominal cross-section aluminum, RM	10 mm <sup>2</sup> - 35 mm <sup>2</sup>
Nominal cross-section aluminum, RE	10 mm <sup>2</sup> - 50 mm <sup>2</sup>
Nominal cross-section aluminum, SM	10 mm <sup>2</sup> - 35 mm <sup>2</sup>
Rated current	- A

GTIN: 4021103809624

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de