

SCREW CONNECTOR, TIN-PLATED CONDUCTOR CROSS-SECTION 10-35 MM², CU, STANDARD VERSION AND AL

Article number: 180962

Connection equipment - screw connectors or branch and connection terminals for kV cast resin joints, shrink joints and mechanical connection and branch joints (MVM and MAM). Screw connector type: Tin-plated with a conductor cross-section of 10 mm² to 35 mm²; Cu and AL only.

Length (mm) 40 mm
Width (mm) 14 mm
Height (mm) 14 mm
Weight (kg) 0,015 kg



Attribute	Value
Protection class (IP)	IP00
Surface protection	verzinkt
Nominal cross-section aluminum, SE	10 mm ² - 35 mm ²
Number of screws	4
Oil stop/center bar	No
Voltage series	bis 15 kV
Conductor material	Aluminium/Kupfer
With soldering hole	No
Nominal cross-section copper, SM	10 mm ² - 35 mm ²
With insulation	No
Nominal cross-section copper, RM	10 mm ² - 35 mm ²
Nominal cross-section copper, RE	10 mm ² - 50 mm ²
Nominal cross-section aluminum, RM	10 mm ² - 35 mm ²
Nominal cross-section aluminum, RE	10 mm ² - 50 mm ²
Nominal cross-section aluminum, SM	10 mm ² - 35 mm ²
Rated current	- A

GTIN: 4021103809624

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de