

**FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 2.5 MM<sup>2</sup>/8 MM**
**Article number: 181006**

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 1. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105 °C - For easy plugging onto fine stranded copper conductors, prevents damage and splicing. Cross section: 2.5 mm<sup>2</sup>; Length without insulation L2: 8 mm; Total length: L1: 15 mm, D1: 2.2; S1: 0.15, S2: 0.25; D2: 4.2; Insulation color: gray; Weight per 100 pieces~kg: 0.01; Packs per piece: 100



|             |            |
|-------------|------------|
| Length (mm) | 155 mm     |
| Width (mm)  | 105 mm     |
| Height (mm) | 5 mm       |
| Weight (kg) | 0,00019 kg |

| Attribute                      | Value               |
|--------------------------------|---------------------|
| Nominal cross-section          | 2.5 mm <sup>2</sup> |
| Surface protection             | verzinkt            |
| Material                       | Kupfer              |
| Color                          | grau                |
| Insulated                      | Yes                 |
| Halogen-free                   | Yes                 |
| Strip goods                    | No                  |
| Total length                   | 15 mm               |
| Design                         | Standard            |
| For short-circuit-proof cables | No                  |
| Insulation material            | Polypropylen (PP)   |
| Sleeve length                  | 8 mm                |
| With identification flag       | No                  |

GTIN: 4021103810064

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de