

**FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 25.0 MM<sup>2</sup>/16 MM**
**Article number: 181022**

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 1. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105 °C - For easy plugging onto fine stranded copper conductors, prevents damage and splicing. Cross section: 25 mm<sup>2</sup>; Length without insulation L2: 16 mm; Total length: L1: 30 mm, D1: 7,3; S1: 0,2, S2: 0,4; D2: 11,2; Insulation color: black; Weight per 100 pieces~kg: 0,13; Packs per piece: 50



Length (mm)	220 mm
Width (mm)	105 mm
Height (mm)	30 mm
Weight (kg)	0,0013 kg

Attribute	Value
Nominal cross-section	25 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Color	schwarz
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	30 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	16 mm
With identification flag	No

GTIN: 4021103810224

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de