

FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 35.0 MM²/16 MM
Article number: 181024

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 1. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105 °C - For easy plugging onto fine stranded copper conductors, prevents damage and splicing. Cross section: 35 mm²; Length without insulation L2: 16 mm; Total length: L1: 30 mm, D1: 8,3; S1: 0,2, S2: 0,4; D2: 12,7; Insulation color: red; Weight per 100 pieces~kg: 0,21; Packs per piece: 1



| | |
|-------------|------------|
| Length (mm) | 195 mm |
| Width (mm) | 127 mm |
| Height (mm) | 25 mm |
| Weight (kg) | 0,00192 kg |

| Attribute | Value |
|--------------------------------|--------------------|
| Nominal cross-section | 35 mm ² |
| Surface protection | verzinkt |
| Material | Kupfer |
| Color | rot |
| Insulated | Yes |
| Halogen-free | Yes |
| Strip goods | No |
| Total length | 30 mm |
| Design | Standard |
| For short-circuit-proof cables | No |
| Insulation material | Polypropylen (PP) |
| Sleeve length | 16 mm |
| With identification flag | No |

GTIN: 4021103810248

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de