

FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 35.0 MM²/25 MM
Article number: 181025

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 1. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105 °C - For easy plugging onto fine stranded copper conductors, prevents damage and splicing. Cross section: 35 mm²; Length without insulation L2: 25 mm; Total length: L1: 39 mm, D1: 8,3; S1: 0,2, S2: 0,4; D2: 12,7; Insulation color: red; Weight per 100 pieces~kg: 0,22; Packs per piece: 1



Length (mm)	175 mm
Width (mm)	120 mm
Height (mm)	40 mm
Weight (kg)	0,00194 kg

Attribute	Value
Nominal cross-section	35 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	rot
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	39 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	25 mm
With identification flag	No

GTIN: 4021103810255

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de