


HEAT-SHRINK TUBING 2:1, BLACK, RAL 9011, THIN-WALLED, Ø 1.1/0.5 MM, L 200 M
Article number: 181600

Polyolefin heat shrink tubing, thin wall design 2:1, black, halogen free and flexible, flame retardant (VW-1/UI224). Technical data: Longitudinal shrinkage: < 5%, Continuous temperature: -55 to 125°C, Shrink temperature: 125°C, Dielectric strength: 15 kV/mm (IEC243), Volume resistivity: 10¹⁴ ohms x cm (IEC93), Tensile strength: 10.4 MPa (ASTM D2671).

Elongation at break: 200 % (ASTM D2671) Ø- in mm; before: 1,1; after: 0,5; Color: black; Wall thickness: 0,33 mm; Length: 200 m;

Packing unit: 1 roll



Length (mm)	300 mm
Width (mm)	300 mm
Height (mm)	25 mm
Weight (kg)	0,24 kg

Attribute	Value
Length	200 m
Material	Polyolefine (PO-X)
Color	schwarz
Execution	dünnwandig
Halogen-free	Yes
Transparent	No
Type	Warmschrumpf
Operating temperature	-45 °C - 125 °C
Nominal cross-section	0.95 mm ² - 0.95 mm ²
Shrinkage rate	2:1
With inside adhesive	No
Inner diameter after shrinkage	0.5 mm
Inner diameter before shrinkage	1.1 mm
Printable	No
Wall thickness after shrinkage	0.33 mm

GTIN: 4021103066812

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de