


**HEAT-SHRINK TUBING 2:1, BLACK, RAL 9011, THIN-WALLED, Ø 19.0/9.0 MM, LENGTH 100 M**
**Article number: 181608**

Polyolefin heat shrink tubing, thin wall design 2:1, black, halogen free and flexible, flame retardant (VW-1/UI224). Technical data: Longitudinal shrinkage: < 5%, Continuous temperature: -55 to 125°C, Shrink temperature: 125°C, Dielectric strength: 15 kV/mm (IEC243), Volume resistivity: 10<sup>14</sup> ohms x cm (IEC93), Tensile strength: 10.4 MPa (ASTM D2671).  
Elongation at break: 200 % (ASTM D2671) Ø- in mm; before: 19,0; after: 9,0; Color: black; Wall thickness: 0,70 mm; Length: 100 m; Packing unit: 1 roll



Length (mm) 450 mm  
Width (mm) 450 mm  
Height (mm) 45 mm  
Weight (kg) 3,85 kg

Attribute	Value
Length	100 m
Material	Polyolefine (PO-X)
Color	schwarz
Execution	dünnwandig
Halogen-free	Yes
Transparent	No
Type	Warmschrumpf
Operating temperature	-45 °C - 125 °C
Nominal cross-section	283.53 mm <sup>2</sup> - 283.53 mm <sup>2</sup>
Shrinkage rate	2:1
With inside adhesive	No
Inner diameter after shrinkage	9 mm
Inner diameter before shrinkage	19 mm
Printable	No
Wall thickness after shrinkage	0.7 mm

GTIN: 4021103066997

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de