

UV AND COLD-RESISTANT CABLE TIES, W X L 3.5 X 140 MM, 100 PIECES
Article number: 181720

UV-resistant cable ties, WxL 3.5x140 mm, cable harness 3-36 mm, in black, made of PA 6.6 with up to 10 times longer service life compared to standard cable ties. Made of 100% UV-resistant black granules. Cold resistant down to - 40°C. Ideal for outdoor use, e.g. in photovoltaic construction. Self-extinguishing, flammability class UL 94 V-2. temperature resistance -40 °C to +85 °C. color black. Certification: UL, RiNA, DNV, LR, Bureau Veritas.

Length (mm)	265 mm
Width (mm)	87 mm
Height (mm)	24 mm
Weight (kg)	0,00061 kg



Attribute	Value
Surface protection	unbehandelt
Material	Kunststoff
Material quality	Polyamid (PA)
Color	schwarz
Execution	innenverzahnt
Fluorescent	No
Halogen-free	Yes
Mounting type	ohne
Detectable	No
Transparent	No
Width of the belt	3.5 mm
Detachable closure	No
Labeling area	ohne
Strap fastener	Kunststoffzunge/-nase
Mounting temperature	-10 °C - 85 °C
Belt length	140 mm
Operating temperature	-40 °C - 85 °C
Bundle diameter	3 mm - 36 mm
Min. holding force	150 N
UL approval	Yes
UV-stable according to ASTM D6779	Yes

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Flammability class of the insulating material according to UL94	V2
Tape thickness	- mm
VG approval	No
MIL approval	No

GTIN: 4021103817209

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de