

UV AND COLD-RESISTANT CABLE TIES, W X L 4.5 X 360 MM, 100 PIECES

Article number: 181724

UV-resistant cable ties, WxL 4.5x360 mm, cable harness 5-101 mm, in black, made of PA 6.6 with up to 10 times longer service life compared to standard cable ties. Made of 100% UV-resistant black granules. Cold resistant down to - 40°C. Ideal for outdoor use, e.g. in photovoltaic construction. Self-extinguishing, flammability class UL 94 V-2. temperature resistance -40 °C to +85 °C. color black. Certification: UL, RiNA, DNV, LR, Bureau Veritas.

Length (mm)	480 mm
Width (mm)	123 mm
Height (mm)	40 mm
Weight (kg)	0,00225 kg



Attribute	Value
Surface protection	unbehandelt
Material	Kunststoff
Material quality	Polyamid (PA)
Color	schwarz
Execution	innenverzahnt
Fluorescent	No
Halogen-free	Yes
Mounting type	ohne
Detectable	No
Transparent	No
Width of the belt	4.5 mm
Detachable closure	No
Labeling area	ohne
Strap fastener	Kunststoffzunge/-nase
Mounting temperature	-10 °C - 85 °C
Belt length	360 mm
Operating temperature	-40 °C - 85 °C
Bundle diameter	5 mm - 101 mm
Min. holding force	220 N
UL approval	Yes
UV-stable according to ASTM D6779	Yes

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Flammability class of the insulating material according to UL94	V2
Tape thickness	- mm
VG approval	No
MIL approval	No

GTIN: 4021103817247

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de