

FLAME-RETARDANT, SELF-EXTINGUISHING CABLE TIES L X W 280 X 4.5 MM, 100 PIECES
Article number: 181731

Fire retardant cable ties made of PA 6.6, flammability class UL 94 V-0. Meets particularly high requirements for flame resistance: the material must not burn for more than 10 seconds and must not ignite flammable materials underneath. Halogen-free, temperature resistance -20 °C to +80 °C. Minimum installation temperature 0 °C. Color milk white.

| | |
|-------------|------------|
| Length (mm) | 400 mm |
| Width (mm) | 113 mm |
| Height (mm) | 34 mm |
| Weight (kg) | 0,00195 kg |



| Attribute | Value |
|---|-----------------------|
| Surface protection | sonstige |
| Material | Kunststoff |
| Material quality | Polyamid (PA) |
| Color | weiß |
| Execution | innenverzahnt |
| Fluorescent | No |
| Halogen-free | Yes |
| Mounting type | sonstige |
| Detectable | No |
| Transparent | No |
| Width of the belt | 4.5 mm |
| Detachable closure | No |
| Labeling area | ohne |
| Strap fastener | Kunststoffzunge/-nase |
| Mounting temperature | 0 °C - 80 °C |
| Belt length | 280 mm |
| Operating temperature | -20 °C - 80 °C |
| Bundle diameter | 5 mm - 76 mm |
| Min. holding force | 175 N |
| UL approval | Yes |
| UV-stable according to ASTM D6779 | Yes |
| Flammability class of the insulating material according to UL94 | V0 |
| Tape thickness | - mm |

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



| | |
|--------------|----|
| VG approval | No |
| MIL approval | No |

GTIN: 4021103817315

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de