

**NON-INSULATED WIRE END FERRULE - TIN-PLATED - 25 MM<sup>2</sup> X 15 MM, 100 PIECES**
**Article number: 182108**

Non-insulated ferrules DIN 46228, part 1 and special dimensions. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated. Design: Cross-section: 25 mm<sup>2</sup>; Length: 18 mm; D1: 7.3; D2: 9.5; S: 0.22; Weight per 100pcs ~kg: 0.07; UL listed: x; Packs of 100 (silver-plated version, on request).

Length (mm)	190 mm
Width (mm)	125 mm
Height (mm)	8 mm
Weight (kg)	0,00072 kg



Attribute	Value
Nominal cross-section	25 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Color	Zinn
Insulated	No
Halogen-free	Yes
Strip goods	No
Total length	15 mm
Design	Standard
For short-circuit-proof cables	No
Sleeve length	15 mm
With identification flag	No
AWG size	4

GTIN: 4021103821084

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de