

**FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 1.5 MM<sup>2</sup>/18 MM**
**Article number: 182205**

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 2. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross section 1.5 mm<sup>2</sup>, length without insulation L2: 18 mm; total length L1: 24 mm; D1: 1.7; S1: 0.15, S2: 0.25; D2: 3.5; insulation color: red, weight per 100 pcs.: 0.02; packing unit: 100.



Length (mm)	140 mm
Width (mm)	100 mm
Height (mm)	4 mm
Weight (kg)	0,00022 kg

Attribute	Value
Nominal cross-section	1.5 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Color	rot
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	24 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	18 mm
With identification flag	No
AWG size	sonstige

GTIN: 4021103822050

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de