

FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 4.0 MM²/18 MM
Article number: 182209

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 2. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross section: 4 mm², length without insulation L2: 18 mm; total length L1: 26 mm; D1: 2.8; S1: 0.2, S2: 0.3; D2: 4.8; insulation color: gray, weight per 100 pcs.: 0.04; pcs.: 100.



Length (mm)	140 mm
Width (mm)	100 mm
Height (mm)	11 mm
Weight (kg)	0,00036 kg

Attribute	Value
Nominal cross-section	4 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	grau
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	26 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	18 mm
With identification flag	No
AWG size	12

GTIN: 4021103822098

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de