

FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 6.0 MM²/18 MM
Article number: 182212

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 2. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross section: 6 mm², length without insulation L2: 18 mm; total length L1: 26 mm; D1: 3.5; S1: 0.2, S2: 0.3; D2: 6.3; insulation color: black, weight per 100 pcs.: 0.06; packing unit: 100.



Length (mm)	170 mm
Width (mm)	102 mm
Height (mm)	11 mm
Weight (kg)	0,0006 kg

Attribute	Value
Nominal cross-section	6 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	schwarz
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	26 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	18 mm
With identification flag	No
AWG size	10

GTIN: 4021103822128

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de