

**FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 25.0 MM<sup>2</sup>/16 MM**
**Article number: 182222**

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 2. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross section: 25 mm<sup>2</sup>, length without insulation L2: 16 mm; total length L1: 30 mm; D1: 7.3; S1: 0.2, S2: 0.4; D2: 11.2; insulation color: brown, weight per 100 pcs.: 0.13; packing unit: 50.



Length (mm)	170 mm
Width (mm)	100 mm
Height (mm)	15 mm
Weight (kg)	0,0013 kg

Attribute	Value
Nominal cross-section	25 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Color	braun
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	30 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	16 mm
With identification flag	No
AWG size	4

GTIN: 4021103822227

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de