


FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 1.0 MM²/8 MM
Article number: 182326

Insulated ferrules according to DIN 46228, part 4 and special dimensions. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro-tinned - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross section: 1 mm²; length without insulation L2: 8 mm; total length L1: 14 mm; D1: 1.4; S1: 0.15; S2: 0.25; D2: 3; insulation color: red; weight per 100 pcs.: 0.01; packing unit: 100.



Length (mm)	145 mm
Width (mm)	105 mm
Height (mm)	4 mm
Weight (kg)	0,00011 kg

Attribute	Value
Nominal cross-section	1 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	rot
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	14 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	8 mm
With identification flag	No
AWG size	16

GTIN: 4021103823262

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de