


FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 35.0 MM²/25 MM
Article number: 182368

Insulated ferrules according to DIN 46228, part 4 and special dimensions. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro-tinned - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross-section: 35 mm²; length without insulation L2: 25 mm; total length L1: 39 mm; D1: 8.3; S1: 0.2; S2: 0.4; D2: 12.7; insulation color: red; weight per 100 pcs ~kg: 0.22; UL listed: x; PU/pc: 50.



Length (mm)	190 mm
Width (mm)	125 mm
Height (mm)	19 mm
Weight (kg)	0,00224 kg

Attribute	Value
Nominal cross-section	35 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	rot
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	39 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	25 mm
With identification flag	No
AWG size	2

GTIN: 4021103823682

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de