


FERRULE INSULATED CROSS-SECTION/SLEEVE LENGTH 70.0 MM²/21 MM
Article number: 182374

Insulated ferrules according to DIN 46228, part 4 and special dimensions. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electroplated tin - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross section: 701 mm²; length without insulation L2: 21 mm; total length L1: 37 mm; D1: 13.5; S1: 0.4; S2: 0.6; D2: 16; insulation color: yellow; weight per 100 pcs.~kg: 0.67; UL listed: -; PU/pc: 25.



Length (mm)	213 mm
Width (mm)	190 mm
Height (mm)	20 mm
Weight (kg)	0,0067 kg

Attribute	Value
Nominal cross-section	70 mm ²
Surface protection	sonstige
Material	Kupfer
Color	gelb
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	37 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	21 mm
With identification flag	No
AWG size	0

GTIN: 4021103823743

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de