

## AL-CU, STANDARD VERSION COMPRESSION CABLE LUG 16 MM<sup>2</sup> M8

### Article number: 183210

AL-CU compression cable lug, 16qmm-M8. Material E-Al and E-Cu according to EN 13600. Filled with contact grease, with plug. Tube dimensions according to DIN 46329, with press markings. For strain-relieved connections of Al cables according to DIN 48201-5 and Al ropes according to DIN EN 50182.



Length (mm)	75 mm
Width (mm)	20 mm
Height (mm)	15 mm
Weight (kg)	0,026 kg

Attribute	Value
Connection thread dimension (metric)	8
Number of fixing holes	1
Code number	12
Material	Aluminium/Kupfer
Color	grau
Nominal cross-section aluminum, RM/SM	16 mm <sup>2</sup> - 16 mm <sup>2</sup>
Narrow flange design	No
Suitable for Al/St ropes	Yes
Cross-sectional shape	rund
Longitudinal density	Yes
Corresponds to DIN	No
Nominal cross-section aluminum, SE	25 mm <sup>2</sup> - 25 mm <sup>2</sup>
St nominal cross-section	- mm <sup>2</sup>

GTIN: 4021103091234

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de