

## AL-CU, STANDARD VERSION COMPRESSION CABLE LUG 120 MM<sup>2</sup> M12

**Article number: 183227**

AL-CU compression cable lug, 120qmm-M12. Material E-Al and E-Cu according to EN 13600. Filled with contact grease, with plug. Tube dimensions according to DIN 46329, with press markings. For strain-relieved connections of Al cables according to DIN 48201-5 and Al ropes according to DIN EN 50182.



|             |          |
|-------------|----------|
| Length (mm) | 107 mm   |
| Width (mm)  | 30 mm    |
| Height (mm) | 22 mm    |
| Weight (kg) | 0,107 kg |

| Attribute                             | Value                                     |
|---------------------------------------|---|
| Connection thread dimension (metric)  | 12  |
| Number of fixing holes                | 1   |
| Code number                           | 22  |
| Material                              | Aluminium/Kupfer                          |
| Color                                 | grau                                      |
| Nominal cross-section aluminum, RM/SM | 120 mm <sup>2</sup> - 120 mm <sup>2</sup> |
| Narrow flange design                  | No  |
| Suitable for Al/St ropes              | Yes                                       |
| Cross-sectional shape                 | rund                                      |
| Longitudinal density                  | Yes                                       |
| Corresponds to DIN                    | Yes                                       |
| Nominal cross-section aluminum, SE    | 150 mm <sup>2</sup> - 150 mm <sup>2</sup> |
| St nominal cross-section              | - mm <sup>2</sup>                         |

GTIN: 4021103091616

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de