

**TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS**
**Article number: 183256**

Tubular cable lugs Cu. Version for fine stranded conductors  
 DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 10 mm<sup>2</sup>; Bolt-Ø: 6 mm; W: 12; Øi: 5,6; Øe: 8; C1: 6; C2: 7; a: 12,6; L: 32; Weight per 100 pcs.-kg: 0,65; Packs of 100



Length (mm) 140 mm  
 Width (mm) 70 mm  
 Height (mm) 70 mm  
 Weight (kg) 0,00653 kg

Attribute	Value
Connection thread dimension (metric)	6
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	10 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	8
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103832561

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de