

TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 25 MM² M 5, 50 PIECES
Article number: 183275

Tubular cable lugs Cu. Version for fine stranded conductors DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 25 mm²; Bolt-Ø: 5 mm; W: 15; Øi: 7,9; Øe:11; C1: 9; C2: 11; a: 16,5; L: 43,5; Weight per 100 pcs.~kg: 1,73; VE/pc. 50



Length (mm)	140 mm
Width (mm)	70 mm
Height (mm)	70 mm
Weight (kg)	0,01725 kg

Attribute	Value
Connection thread dimension (metric)	5
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	25 mm ²
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	4
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103832752

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de