

**TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 35 MM<sup>2</sup> M 6, 1 PIECE**
**Article number: 183286**

Tubular cable lugs Cu. Version for fine stranded conductors DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 35 mm<sup>2</sup>; Bolt-Ø: 6 mm; W: 18; Øi: 9,2; Øe: 12,5; C1: 7; C2: 10; a: 18,5; L: 43,5; Weight per 100 pcs.~kg: 2,08; PU/pc. 1



Length (mm)	44 mm
Width (mm)	18 mm
Height (mm)	15 mm
Weight (kg)	0,02084 kg

Attribute	Value
Connection thread dimension (metric)	6
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	35 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	2
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103832868

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de