

**TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 50 MM<sup>2</sup> M 12, 1 PIECE**
**Article number: 183302**

Tubular cable lugs Cu. Version for fine stranded conductors DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 50 mm<sup>2</sup>; Bolt-Ø: 12 mm; W: 21; Øi: 11; Øe: 15; C1: 10; C2: 14; a: 21,5; L: 55,5; Weight per 100 pcs.~kg: 3,56; Packs per pc. 1



|             |            |
|-------------|------------|
| Length (mm) | 55 mm      |
| Width (mm)  | 22 mm      |
| Height (mm) | 17 mm      |
| Weight (kg) | 0,03562 kg |

| Attribute                            | Value              |
|--------------------------------------|--------------------|
| Connection thread dimension (metric) | 12                 |
| Connection bracket                   | 180° (horizontal)  |
| Number of fixing holes               | 1                  |
| Nominal cross-section                | 50 mm <sup>2</sup> |
| Surface protection                   | verzinkt           |
| Material                             | Kupfer             |
| Insulated                            | No                 |
| AWG size                             | 0                  |
| Narrow flange design                 | No                 |
| Flange shape                         | Ringform           |
| With viewing hole                    | No                 |
| Ladder class                         | K1.5 = feindrätig  |

GTIN: 4021103833025

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de