

TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 70 MM² M 14, 1 PIECE
Article number: 183314

Tubular cable lugs Cu. Design for fine stranded conductors according to DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 70 mm²; Bolt-Ø: 14 mm; W: 24; Øi: 13,1; Øe: 17; C1: 13,5; C2: 15,5; a: 27,5; L: 67,5; Weight per 100 pcs.~kg: 4,93; Packs per pc. 1



Length (mm) 67 mm
 Width (mm) 25 mm
 Height (mm) 19 mm
 Weight (kg) 0,04933 kg

Attribute	Value
Connection thread dimension (metric)	14
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	70 mm ²
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	0
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103833148

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de