

TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 120 MM² M 10, 1 PIECE
Article number: 183330

Tubular cable lugs Cu. Design for fine stranded conductors according to DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 120 mm²; Bolt-Ø: 10 mm; W: 30; Øi: 16,2; Øe: 21; C1: 17; C2: 17; a: 31,5; L: 80; Weight per 100 pcs. ~kg: 8,83; PU/pc. 1



Length (mm)	75 mm
Width (mm)	30 mm
Height (mm)	24 mm
Weight (kg)	0,08826 kg

Attribute	Value
Connection thread dimension (metric)	10
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	120 mm ²
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	250 kcmil
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103833308

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de