

**TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 150 MM<sup>2</sup> M 10, 1 PIECE**
**Article number: 183340**

Tubular cable lugs Cu. Design for fine stranded conductors according to DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 150 mm<sup>2</sup>; Bolt-Ø: 10 mm; W: 33; Øi: 18; Øe: 23; C1: 17; C2: 18; a: 31,5; L: 89; Weight per 100 pcs.~kg: 11,13; Packs per pc. 1



Length (mm)	81 mm
Width (mm)	33 mm
Height (mm)	27 mm
Weight (kg)	0,1128 kg

Attribute	Value
Connection thread dimension (metric)	10
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	150 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	300 kcmil
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103833407

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de